

Calcium Chloride



CaCl₂·2H₂O



Molar mass: 147.014 g/mol Density: 1.835 g/cm³ Melting Point: 176 °C

Boiling Point: 1935 °C (anydrous) CAS Number: 10035-04-8

Uses: Chemical industry, oil drilling, snow and ice meltin, soil conditioning

Technical Data Sheet

recillical Data Sileet	
Grade	95% Technical Grade
Appearance	White Granular or Flake
Calcium Chloride as CaCl ₂	95% min.
Total Alkali Chlorides as NaCl	5% max.
Magnesium as MgCl₂	0.5% max.
Calcium Hydroxide	0.20% max.
Calcium Carbonate	0.20% max.
Sulfate	0.20% max.
Iron	0.01% max.
Heavy Metal (Pb)	0.005% max.

Packaging Options

25 kg. Plastic woven bag or 1000 kg Big bag



Container Options

20 ft. Container 22-24 mt per FCL



Available Carriers

















DAN<mark>GER! MAY BE FATAL IF SW</mark>ALLOWED. HARMFUL IF INHALED. MAY CAUSE IRRITATION TO SKIN, EYES, AND RESPIRATORY TRACT. AFFECTS MUSCLES (INCLUDING THE HEART), AND CENTRAL NERVOUS SYSTEM.

Current Destinations



The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc., given herein may change without prior information and do not stitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and

